

VACUUM SENTRY

Combining unmatched performance with ultimate productivity, The Vacuum Sentry (V640 Series) guards system service activity and provides notification when pre-set alarm thresholds are reached. Choose from the VG640 with local audible and visual alarms or the VG640T which adds the remote alarm receiver (R100) with audible, visual and vibration alarms.

MADE IN THE
USA 

Features / Benefits

- Unmatched Resolution (as low as 0.5 micron)
- ½ Second Response Time (update rate)
- Backlit LCD
- Local Audible and Visual Alarm
- Radio Frequency (RF) Transmission Signal (VG640T)
- Auto Shut Off
- Built-in Hanger
- User Addressable Remote Alarm(R100) available (Operates with VG640T only)
- One Year Warranty

Applications

- Vacuum Measurements During System Evacuation
- Measurements to Confirm System Leaks
- High Precision Laboratory Tests

Models

VG640	Vacuum Sentry with Local Alarms
VG640T	Vacuum Sentry with Local Alarms & Remote Alarm (R100 included)
R100	Remote Alarm receiver (Audible, Visual & Vibration)



"Green" Backlight



"Red" Indicates Alarm Condition



Front (R100)



Integrated Belt Clip

Application Note

While the technician is servicing another system, the VG640T can send a signal to the remote alarm (R100) up to 400 feet away.

VG640/VG640T Specifications

Sensor Type	Thermistor	
Connector Type	Standard ¼ inch male flare fitting.	
Vacuum Range	0 – 19,000 Micron (0 – 2,600 Pascal).	
Resolution	Measurement Range	Resolution
	0-140:	0.5 Micron
	140-400:	1 Micron
	400-800:	2 Micron
	800-2000:	5 Micron
	2000-6000:	20 Micron
	6000-9000:	100 Micron
	6000-16000:	200 Micron
	16000-19000:	1000 Micron
Units	Micron, milliBar, Pascal, Torr, milliTorr	
Accuracy	+/-10% or +/-10 Micron, whichever is larger (50 to 2000 Microns) at 75°F	
Update Rate	0.5 sec.	
Alarm	Audible and visual alarm for high and low vacuum	
Remote Alarm (R100)	Up to 400ft* remote audible, visual and vibrating alarm for high and low vacuum	
Alarm Volume	87 dB for both unit and remote	
Operating Temperature Range	0°F to 150°F (-17°C to 65°C)	
Overpressure	800 PSI max (55 Bar)	
Power Source	3 AA Batteries	
Battery Life	600 Hours continuous usage, with battery indicator.	
Auto Shutoff	8 hours when alarms are active. When alarms are disabled: <ul style="list-style-type: none">• 10 minutes when vacuum reading is above 19,000 Microns• 1 hour when vacuum reading is below 19,000 Microns	
Weight	6 oz	
Dimensions	5.5" H X 2.75" W X 1.5" D	

*Distance is measured when the remote receiver is within a direct line of sight of the VG640T. Obstructions between the remote and the VG640T can reduce this distance.

R100 Remote Alarm Receiver Specifications

Distance from VG640T	Up to 400 ft*
Alarm	Audible, visual and vibrating alarm
Alarm Volume	87 dB
Operating Temperature Range	-20°F to 160°F (-28°C to 70°C)
Power Source	9 V Battery
Battery Life	45 Hours continuous usage, with low battery audible indicator.
Weight	3 oz
Dimensions	5.0" H X 2.5" W X 1.0" D

*Distance is measured when the remote receiver is within a direct line of sight of the VG640T. Obstructions between the remote and the VG640T can reduce this distance.

VGC
Vacuum Gauge Coupler

Insures leak free connection to vacuum gauge during measurement.



VG64S
Single Port
Digital
Vacuum Gauge



VG64
Digital
Vacuum Gauge



MORE PRODUCT CHOICES

With resolution as low as 1 micron and 1/2 second response time, the VG64 provides accurate measurements, FAST. It makes evacuating a system EASY.

Features/Benefits

- Ultra Fine Resolution (as low as 1 Micron)
- 1/2 Second Response Time
- Auto Shut Off
- Built in Hanger
- Easy Access Cleaning Port
- Measures Vacuum in 7 International Units

Accessories

VGC	Vacuum Gauge Coupler
10475	120 Volt AC Adapter
10740	Vinyl Case